

# Thermo Scientific Masterflex

## P/S Standard Digital Pump Systems



Masterflex® P/S Pump Systems

Thermo Fisher Scientific combines digital control with peristaltic pump technology to provide high-accuracy, maintenance and worry free performance to your chemical feed applications.

- Menu-driven LCD graphical interface provides easy system set-up.
- Loaded with a broad range of remote control options—ideal for automated process applications.
- The brushless motor driven by a PWM control is capable of a flow range turndown of 380,000:1.
- Other control capabilities include programmable dispensing by volume, time, or copy modes with a programmable delay between cycles for convenient, automated dispensing.
- Precise PWM speed control ( $\pm 0.1\%$ ) maximizes accuracy and efficiency while the brushless motor gives you quiet, maintenance-free reliability.
- Optimize system accuracy by calibrating the pump system in process. The calibration is stored in memory—one calibration value per tubing size.
- Program the drive via the simple membrane keypad and multi-language display.
- Reversible motor so you can purge tubing before or after pumping.
- IP33 rated ABS housing for improved splash and dust resistance.

**Holland**<sup>®</sup>  
**APPLIED TECHNOLOGIES**

Indianapolis • Chicago • San Juan  
[www.hollandapt.com](http://www.hollandapt.com)  
800-800-8464



ISO9001:2000  
SUPPLIER CERTIFIED

2 year  
warranty



P/S 3 9/1/09

## Flow rates in mL/min (flow rates in parentheses can only be obtained with the High-Performance Pump Head)

RPM	Precision pump tubing						High-performance precision pump tubing*			
	P/S 13	P/S 14	P/S 16	P/S 25	P/S 17	P/S 18	P/S 15	P/S 24	P/S 35	P/S 36
0.1 to 600	0.006 to 36	0.021 to 130	0.08 to 480	0.17 to 1000	0.28 to 1700	0.38 to 2300	0.17 to 1000 (0.18 to 1100)	0.28 to 1700 (0.30 to 1800)	.38 to 2300 (0.43 to 2600)	0.48 to 2900 (0.57 to 3400)
0.02 to 100	0.001 to 6	0.004 to 21	0.016 to 80	0.033 to 170	0.057 to 280	0.077 to 380	0.033 to 170 (0.033 to 180)	0.057 to 280 (0.057 to 300)	0.077 to 380 (0.077 to 430)	0.096 to 480 (0.096 to 580)

\* Values in parentheses are with high-performance Pump Heads

## Specifications & Ordering Information

Catalog number	1300-3600-955	1300-3600-956	1300-3600-965	1300-3100-955	1300-3100-956	1300-3100-965
Included Pump Head	EASY-LOAD II (thin wall)	EASY-LOAD II (thick wall)	High-Performance (thick wall)	EASY-LOAD II (thin wall)	EASY-LOAD II (thick wall)	High-Performance (thick wall)
Number of heads accepted	2	2	1	4	4	1
RPM	0.1 to 600			0.02 to 100		
External control – input	0 to 20 mA, 0 to 10V; Scaleable START/STOP, DIR. (CW/CC), PRIME via contact closure Remote / Local Enable Contact Secondary Speed Control 0-20mA or 4-20mA Auxiliary Contact (Limit Switch)					
External control – output	4 to 20 mA, or 0 to 10 V					
Motor running logic	N.O. or N.C. (1A @ 24V)					
Tachometer output	5V, TTL pulse					
Power supply output	24 V, 150 mA					
Voltage (50/60 Hz)	115/230 V AC (auto selected)					
Motor type	Brushless continuous duty, TENV*, DC, permanent lubricated bearings					
Control type	PWM (Pulse Width Modulated)					
Speed regulation (repeatability)	±0.1%; ±0.1 rpm @ 600 rpm; %; ±0.21 rpm @ 100 rpm					
Operating temperature	0 to 40°C (32 to 104°F)					
Storage temperature	-25 to 65°C (-13 to 149°F)					
Housing materials	ABS, Powder-coated aluminum					
IP rating	IP33					
Agency approvals	ETL, cETL, CE					
Controller dimensions (L × W × H)	13.0 × 8 × 8					
Shipping weight	20 lbs.					

**Holland**<sup>®</sup>  
**APPLIED TECHNOLOGIES**  
 Indianapolis • Chicago • San Juan  
[www.hollandapt.com](http://www.hollandapt.com)  
 800-800-8464

©2009 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change.

P/S 4 9/1/09

Fluid Handling

Barrington, IL  
60010

1-800-637-3739  
1-847-381-7050  
1-847-381-7053 fax

[www.thermo.com/fluidhandling](http://www.thermo.com/fluidhandling)

**Thermo**  
SCIENTIFIC