



FLOW  
LEVEL  
PRESSURE  
ANALYTICAL  
TEMPERATURE  
INSTRUMENTATION  
PASTEURIZATION CONTROLS

**Holland**  
APPLIED TECHNOLOGIES  
Indianapolis Chicago San Juan  
www.hollandapt.com  
800-800-8464

## AWESOME 1/8 DIN Panel Meter

### Know Exactly When Your Critical Process Values Change!

- 27% larger than other 1/8 DIN panel meters - .71" high LED's
- Red display is 20% brighter than other panel meters
- Programmable color change based on an event
- Minimum & maximum values saved until re-set

A key process value - do your operators have one? Is it easy to monitor? With the AWESOME 1/8 DIN panel meters, featuring big, bright, color-changing displays, keeping track of it is even easier!

Analog input models for temperature, pressure, level, and flow as well as digital input models such as rate meters, indicators, counters and timers are available. These intelligent units offer multiple relay & alarm outputs, optional serial communication, and specialized functions on analog input units. With 13 models to choose from, the process value you require

can surely be displayed. The minimum and maximum values along with total alarm time may be saved until re-set.

In fact, your key process value will be displayed on the biggest and brightest 1/8 DIN display in the industry. The AWESOME family features a 0.71" high LED (27% larger than ordinary 1/8 DIN units) with advanced, brilliant red, gallium arsenide technology. Not only is the display large and striking, but it can also *change color*. The display can be programmed to change from red to green or green to red at a preset value.

Easy programming makes these units even more desirable. All models are programmed via the front panel and are scalable to display inputs in engineering units. In addition to showing parameter values on the primary display, a help function can be utilized to show parameter descriptions. The secondary legend also indicates which value is shown on the primary display via a single digit character.

Detailed specifications and ordering information can be found on the reverse, or by visiting our website at [www.andinst.com](http://www.andinst.com).



# Specifications

## Unique Model Specifications

### ANALOG INPUT MODELS

#### Sensor/Process Inputs

Type: Temp. Ind.: B, J, K, N, S & T thermocouples, 3 & 4 wire RTDs

DC Process: to 50 mA,  $\pm 10$  VDC,  $\pm 100$ mV

AC Volts/Amps: from 0-1VAC to 0-600 VAC, 0-1mA to 0-1 amp

DC Volts/Amps: from 0-100mV to 0-600 VDC, 0-1mA to 0-2 amps

Strain Gauge: 0-100 mVDC

**Accuracy:**  $\pm 0.1\%$  of span ( $\pm 0.01\%$  of span for DC Process;  $\pm 0.03\%$  of span for Strain Gauge)

**Sample Rate:** 250ms (100ms for DC Process & Strain Gauge)

**Resolution:** 14 bits

**Sensor Break:** Detected w/in 2 secs. (N/A to AC & DC Volts/Amps)

### DIGITAL INPUT MODELS

#### Count/Time Inputs

Type: Sinking/Sourcing or Contact Closure (Quadrature for Counters)

Frequency: 10 kHz max. (5 kHz max. for Position Indicator)

Magnetic Input: 0.5 to 90V peak (only for Rate and Rate w/Total)

Logic: Low  $\leq 2.0$  VDC, High  $\leq 3.0$

Response Time: 25 ms

Impedance: 4.7 k-ohms to + Voltage

Function: Digital Input Models: Input 1: Remote Reset (Display Hold on Rate Meter Model), Input 2: Security Lockout Analog Input Models: Programmable

## Common Specifications

### Outputs

Solid State: NPN open collector, 30 VDC max. 100 mA max.

Relay: SPDT, 5A resistive @ 110 VAC

Latency: 75 $\mu$  seconds, plus 8 ms for relay pull-in

Linear Outputs: (N/A for Totalizer or Counters) 0-20mA, 4-20mA, 0-10V, 2-10V 0-5V, 1-5V (field selectable).

### Electrical

Supply Voltage: 90-264 VAC, 50-60Hz, or 20-50 VAC/VDC.

Power Consumption: 4 Watts

Access Power Supply: 9-15 (unregulated VDC), 125mA max. - digital 24 (regulated VDC), 30mA max. - analog

### Display

Type: Red/Green, 7 segment LED, 5-digit primary display, single digit secondary display

Height: 0.71" (18mm) primary display, 0.3" (7mm) secondary display

Annunciators: Output 1 & 2 status

### Physical

Dimensions: 48mm (1.89") x 96mm (3.78"), 110 mm (4.33") deep

Mounting: Panel mount (bracket supplied), 45mm (1.77") x 92mm (3.62") cutout

Terminals: Screw type - combination head

Front Panel Rating: NEMA 4X / IEC IP65

Weight: 0.56 lbs.

### Environmental

Operating Temp.: 0° to 55° Celsius, 32° to 131° Fahrenheit

Storage Temp.: -20° to 80° Celsius, -4° to 176° Fahrenheit

Relative Humidity: 20% to 95% non-condensing

Approvals: CE

